

# SHIELD Šindra • Samolepljiva šindra



>>> ArmourShield® (27) Ultra dva tona smeđa



# SHIELD Šindra • Samolepljiva šindra

## Vaše prednosti:

- Samolepljiva šindra
- Može se koristiti na vrlo strmim krovovima
- Izvrsna otpornost na kišu nošenu vetrom i ledene brane



Armourshield®



Diamantshield®

<b>Dužina</b> (EN 544)	1000 mm (± 3)	1000 mm (± 3)
<b>Širina</b> (EN 544)	318 mm (± 3)	284 mm (± 3)
<b>Težina</b>	± 9,2 kg/m <sup>2</sup>	± 11,2 kg/m <sup>2</sup>
<b>Pokrivnost/paket</b>	3 m <sup>2</sup>	2,46 m <sup>2</sup>
<b>Šindre/paket</b>	22	22
<b>Paketi/paleta</b>	42	36

<b>Adhezija granula</b> (EN 12039)	max. 1,2 g	max. 1,2 g
<b>Zatezna dužina*</b> (EN12311-1)	1000 N/50 mm	1000 N/50 mm
<b>Zatezna širina*</b> (EN12311-1)	700 N/50 mm	700 N/50 mm
<b>Istezanje dužina*</b> (EN12311-1)	3,50 %	3,50 %
<b>Istezanje širina*</b> (EN12311-1)	3,50 %	3,50 %
<b>Otpornost na trganje*</b> (EN 12311-1)	160 N	160 N
<b>Otpor na vetar</b> (tunel test: 10°)	220 km/h	-

<b>Spoljašnje požarne performanse</b>	B <sub>roof</sub> T <sub>1</sub>	B <sub>roof</sub> T <sub>1</sub>
<b>Reakcija na vatru</b>	E klasa	E klasa

\* Registrovane prosečne vrednosti



IKO Sales International NV

I.Z. Ravenshout 3.9 74 • Truibroek 74 • 3945 Ham • Belgium

T +32 (0)11 34 01 20 • F +32 (0)11 34 01 30 • E support@iko.be • [www.iko.be](http://www.iko.be)

 **IKO**  
The Shingles Expert

Informacije su podložne promeni bez prethodnog obaveštavanja.

Za više informacija posetite [www.iko.be](http://www.iko.be) u vezi sa proizvodima i dostupnim bojama